

High Voltage XLPE Cable Data

66kV Aluminium Milliken, Water Blocked

Description: 66 kV Aluminium, XLPE, Corrugated Seamless Aluminium (CSA), #LLDPE Graphite

Specification: SANS/IEC 60840/ NRS 077, Fully Water Blocked

Last updated: December 2025

PHYSICAL									
Conductor size	mm ²	1200	1600	2000	2500				
Conductor diameter	mm	43,4	51,0	56,1	63,4				
Diameter over s/c conductor screen	mm	48,4	55,6	61,1	67,2				
Diameter over XLPE insulation	mm	67,3	74,9	80,7	87,0				
Diameter over s/c core screen	mm	70,5	77,9	83,6	90,1				
Diameter over CSA sheath	mm	90,4	98,1	104,1	110,8				
Final diameter of cable (D)	mm	103,6	111,3	117,3	124,0				
Cable mass (approximate)	kg/m	10,6	12,4	14,2	16,6				
Gross mass (500 m) (approximate)	kg	6700	7610	8470	9680				
Minimum installation bending radius	m	3,11	3,34	3,52	3,72				
DC Resistance @ 20°C	Ω/km	0,0247	0,0186	0,0149	0,0119				
Max Electric stress at conductor screen	kV/mm	4,77	4,59	4,49	4,40				
Min Electric stress at insulation screen	kV/mm	3,43	3,41	3,40	3,40				
Capacitance	µF/km	0,421	0,465	0,500	0,538				
Zero Sequence Resistance @ 90 °C	Ω/km	0,0926	0,0803	0,0723	0,0650				
Zero Sequence Reactance @ 90 °C	Ω/km	0,0568	0,0522	0,0501	0,0466				
ELECTRICAL RATINGS (FORMATION BASED)									
		Tref	*Flat	Tref	*Flat	Tref	*Flat	Tref	*Flat
Current rating in ground	Amps	863	969	977	1128	1066	1261	1157	1411
Current rating in air in shade	Amps	1328	1633	1552	1959	1729	2230	1928	2568
AC Resistance @ 90 °C	Ω/km	0,0319	0,0318	0,0241	0,0241	0,0195	0,0194	0,0157	0,0156
Reactance	Ω/km	0,114	0,172	0,109	0,167	0,106	0,164	0,102	0,160
Impedance	Ω/km	0,119	0,175	0,111	0,169	0,108	0,165	0,103	0,161
Sheath standing voltage outer phases	V/km	49,6	125,0	55,3	144,0	59,6	160,0	63,9	178,0
SHORT CIRCUIT RATINGS									
Symmetrical fault rating (250 °C)	kA (1 s)	113,0		151,0		189,0		236,0	
Earth fault rating (150 °C)	kA (1 s)	43,1		46,7		49,6		52,8	

*Note LLDPE default, datasheet applicable for MDPE and HDPE where required.

The current ratings above are based on standard laying conditions for a single circuit in isolation as follows:

- Conductor temperature = 90 °C
- Soil thermal resistance = 1,2 K·m/W
- Soil temperature = 25 °C
- Air temperature = 30 °C
- Depth of burial = 1200 mm
- * Flat spacing 2D
- ±5% tolerance on dimensions



DISCLAIMER: CBI reserves the right to change product specifications from time to time to effect improvements and /or enhancements and accepts no liability arising from any difference between the published parameters of this data sheet and the finished product, unless by prior written agreement.

POWER BY INNOVATION... INNOVATION THROUGH PARTNERSHIPS

CBI electric: african cables | a division of ATC Pty Ltd | Registration No. 1955/003773/07
 PO Box 172, Vereeniging 1930 | 1 Steel Road, Peacehaven, Vereeniging, 1939, South Africa
 Tel: +27 16 430 6000 | www.cbi-electric.com | a Reunert company | B-BBEE Level 1
 ISO 9001 | ISO 14001 | ISO 45001